



Medium Fire Alarm System

P/NFAMEDSEC900.1 "Now available on our GSA Schedule"

Medium Fire Alarm System

The solution is designed around medium applications of IDC and NAC Devices. The solution System consists of a Dual Loop Addressable Fire Alarm Panel with a capacity of 563 points. Panel has drift compensation, day/night automatic sensitivity, two levels of maintenance alerts, with cross listings for releasing and low pressure CO2 service. The panel comes with a full size red box and a separate battery box with two (2) each 12 Volt 55 AH batteries, 25 each Intelligent Addressable Smoke Detectors with Bases; four (4) each Intelligent Addressable Heat Detectors with Bases; eight (8) Intelligent Addressable Pull Stations; four (4) each Addressable Monitor Modules; four (4) each Control Modules; three (3) each Intelligent Duct Detectors with Keyed Remote Test Stations and Sampling Tubes; one (1) each 80 Character LCD Annunciator with Backbox; 12 each Horn/Strobes, 24 Volt 15/75Cd; four (4) each Strobe Only Units, 24 Volt 15/75Cd.; 8,000 feet 16/2 FPL Wire, and 1,000 feet of ¾-inch EMT Conduit with Connectors, Couplings, Straps, Junction Boxes and Covers. System design, engineering, fabrication, installation, programming, test, checkout and system certification are included.

4230 Beechwood Drive, Greensboro, NC 27410, info@sigcom.net
Phone 336-547-9700, Fax 336-547-1449

Contents Copyright 2003 SIGCOM, All Rights Reserved

<http://www.sigcom.net/commpricelist/commpricelist.htm>