



Basic 20 Zone Perimeter Fence Protection Security System with One Microwave Zone (5000-foot Perimeter)

P/N PPS-19/1SEC1000.1 "Now available on our GSA Schedule"

Basic 20 Zone Perimeter Fence Protection Security System with One Microwave Zone (5000-foot Perimeter)

Nineteen (19) Zones, double-run ruggedized Transducer Sensor Cable, one (1) microwave zone at Rear Vehicle Sallyport, Head-end 20 Zone Monitor and Control, External Printer, Battery Backup and Control Unit housed in GFE Rack. Fence Transponders installed in 20 inch by 20 inch x 8 inch Nema with 12 enclosures on 4 inch posts on fence perimeter. Includes grounding rods, fence clamps, power, data wiring, and conduit. Engineering, installation services, onsite training and travel are included.

The outdoor security business has been simplified. The advanced Perimeter Fence Protection Security System approaches the outdoor environment differently. Now there are no more complex electronics hanging on cold, wet and windblown fences. No more complicated multiplex addresses. No more juggling with advanced instruments while trying to decide about the bandwidth, count, gain and time. The Perimeter Fence Protection Security System is the simple solution to outdoor security. It allows you to do remarkable things from the comfort of an indoor control center, not in the middle of a driving rainstorm or in the teeth of a blizzard. The Perimeter Fence Protection Security System uses highly advanced global signal processing to learn the characteristics of your site and exterior disturbances. The system employs that information to reduce nuisance alarms. Each zone processor has an adjustment for the sensitivity of that particular zone. The Contractor shall provide equipment, parts, conduit, wire, and labor to install a Perimeter Fence Protection Security System.

4230 Beechwood Drive, Greensboro, NC 27410, info@sigcom.net
Phone 336-547-9700, Fax 336-547-1449

Contents Copyright 2003 SIGCOM, All Rights Reserved

<http://www.sigcom.net/commpricelist/commpricelist.htm>

The system will consist of the following:

1. Nineteen (19) fence zones and one (1) microwave zone. A double run of electret transducer cable will be installed around the entire fence perimeter to include the rear sallyport, sallyport wing fences, and 20 linear feet of buffer fences that intersect the main perimeter. The microwave zone will be located at the rear sallyport and will protect the interior sallyport slide gate of the sallyport.
2. Head-end equipment will consist of a rack mountable annunciator controller, external printer, battery backup, and a central controller. All head-end equipment will be housed in government furnished racks/shelves.
3. Dual fence zone transponders will be installed inside 20-inch by 20-inch by 8-inch Nema 12 enclosures mounted on 4-inch posts around the perimeter.
4. The conduit system will consist of 1 ¼-inch rigid galvanized conduit and will be attached to the fence approximately 12 inches above grade. The conduit will attach to the fence posts by means of a 2-inch conduit hanger and a 1 ½-inch PVC bushing. The PVC bushing acts as an insulator between the conduit and the fence post to alleviate excessive noise caused by the expansion and contraction of the conduit. Expansion joints and pulling points will be installed.
5. Ground rods will be installed at each transponder and microwave location and at or near the location of the head-end equipment for grounding.
6. Onsite training for both operation and maintenance of the new system will be provided.

**4230 Beechwood Drive, Greensboro, NC 27410, info@sigcom.net
Phone 336-547-9700, Fax 336-547-1449**

Contents Copyright 2003 SIGCOM, All Rights Reserved

<http://www.sigcom.net/commpricelist/commpricelist.htm>