



## *Interior/Exterior Perimeter Fence*

### **P/N PSFTOPSEC1000.1**

#### **Interior/Exterior Perimeter Fence *"Now available on our GSA Schedule"***

This Interior/Exterior Perimeter Fence solution is designed standard for the Federal Bureau of Prisons (FBoP) Perimeter. SIGCOM will provide and install fence using the FBoP Technical Design Guidelines, Issue Date:01-31-01. Security Fences and Gates Section 02820-1 through 02820-12, and drawings 02820-D1 through 02820-D23. Barbed Tape is based on section 02835-1 through 02835-3. Installation is based on favorable conditions; therefore, unusual circumstances will require onsite review and costing. Location, identification and relocation, if necessary, of underground obstructions/utilities are the responsibility of the owner.

#### **EXCLUDES:**

*Concrete sidewalk, concrete mow strip, 6 mil poly weed barrier, soil sterilization, excavation for and placement of crushed stone.*

#### **Exterior Perimeter Fence – Low and Medium Perimeter Security Fence**

- 3660 mm (12') High.
- Chain Link Fabric - #9 gauge (.148") x 50 mm (2") mesh with top and bottom selvages twisted and barbed. Fabric finish – Aluminum coated per ASTM A491.
- Terminal Posts - 102 mm (4"OD).
- Line (intermediate) posts - 73 mm (2.875"OD), spaced at 3050 mm (10') O.C.
- Top, intermediate, and bottom rails - 42 mm (1.66"OD).
- Barbed Tape 750 mm (30") diameter, includes ground stakes @ 2000 mm (6'-6") O.C.;
- 5 rows Type B – Wire reinforced.
- 4 rows Type A – Non-reinforced.

#### **Interior Perimeter Fence – Low and Medium Perimeter Security Fence**

- 3660 mm (12') High.
- Chain Link Fabric - #9 gauge (.148") x 50 mm (2") mesh with top & bottom selvages twisted and barbed. Fabric finish – Aluminum coated per ASTM A491.
- Terminal Posts - 102 mm (4"OD).
- Line (intermediate) posts - 73 mm (2.875"OD), spaced at 3050 mm (10') O.C.
- Top, intermediate, and bottom rails - 42 mm (1.66"OD).
- Barbed Tape 750 mm (30") diameter, includes ground stakes @ 2000 mm (6'-6") O.C.;
- 1 row Type B – Wire reinforced.

#### **EXCLUDES:**

*Concrete sidewalk, concrete mow strip, 6 mil poly weed barrier, soil sterilization, excavation for and placement of crushed stone.*

**4230 Beechwood Drive, Greensboro, NC 27410, [info@sigcom.net](mailto:info@sigcom.net)  
Phone 336-547-9700, Fax 336-547-1449**

Contents Copyright 2003 SIGCOM, All Rights Reserved

<http://www.sigcom.net/commpricelist/commpricelist.htm>